

Design, manufacture and supply communication systems world wide for use in the petrochemical industry.

KB010 Packing And Preservation Procedure Type C3 Case

| | | |
|-----------------------|-------|---|
| Uses | C3.1 | Road, Air or Seafreight |
| | C3.2 | Highly recommended for all Electrical/Electronic and vulnerable equipment |
| | C3.3 | Recommended where climatic conditions and transport are arduous (poor roads) for both Northern and Southern hemispheres, as sheathing boards interlock, making a stronger case |
| | C3.4 | May be loaded to shipping container |
| Specifications | C3.5 | All equipment enclosed in barrier foil bag and hermetically sealed. For smaller difficult to bag items such as cartons etc the case internal walls will be foil lined. This will replace the moisture repellent lining C3.6 |
| | C3.6 | Case to be lined with moisture repellent material |
| | C3.7 | Desiccant enclosed to required amount as per formula* for a minimum of 6 months |
| | C3.8 | Vertical type with either 16mm or 22mm boards. As an alternative 9mm ply can also be used |
| | C3.9 | Base boards – as above |
| | C3.10 | Sheathing and lid – as above |
| | C3.11 | Internal packing timbers are enclosed in foil, and have a 4mm thick Foam/felt cushion, where they touch equipment |
| | C3.12 | Internal packing timbers – 75 x 100mm. 75 x 50mm or 75 x 150mm as appropriate |
| | C3.13 | Underside of lid lined with barrier foil, and supported by corrugated plastic to prevent the ingress of water, with the addition of heavy duty reinforced woven polyester covering the lid boards |
| | C3.14 | Equipment is firmly bolted to base and or secured by way of internal bracing timbers |
| | C3.15 | Suitable for containerised and conventional sea journeys |
| Markings | C3.16 | All international symbols used |
| | C3.17 | Lifting points to be identified for handling by way of crane or forklift |
| | C3.18 | Weights and sizes to be applied to sides of case by way of indelible black ink |
| Limitations | C3.19 | Desiccated for six months, case should be unpacked prior to the Date shown on the side of the case |
| Storage | C3.20 | Long term storage for up to six months without additional Desiccation |

This specification is our highest standard, well tried and tested, and the ultimate in protection, both from man and the elements

*Can be desiccated for longer periods

The above specification complies with BS1133. Refer to BS1133 for Illustration & Design

For your local office please contact:

Head Office

VODEC

Industrial Communications Ltd

Vodec Industrial Communications Ltd,
Parkview, Lockwood Close
Nottingham,
NG5 9JN,
England,

Tel: +44 (0) 115 967 5240

Fax: +44 (0) 115 967 5241

E-mail: sales@vodec.com

Web: www.vodec.com

Regional Offices



VODEC U
A

Vodec-USA LLC,
PO BOX 15
Carencro
LA 70520

United States of America

Tel: +1 337 326 5395

Fax: +1 337 406 0999

E-mail: sales@vodec-usa.com

Web: www.vodec-usa.com



VODEC
ASIA PACIFIC

Vodec Asia Pacific Sdn. Bhd
Suite E-10-5 Megan Avenue 1,
189 Jalan Tun Razak
50450 Kuala Lumpur
Malaysia

Tel: +60 3-21669580

Fax: +60 3-21669807

Email: sales@vodec-asiapac.com

Web: www.vodec-asiapac.com



VODEC

Vodec France
11, rue Emile Roux
94120 Fontenay-Sous-Bois
France

Tel: +33 (0) 141951849

Fax: +33 (0) 141951849

Email: sales@vodec-france.com

Web: www.vodec-france.com